

DSS/Dancoo S Standard / Tech features

1 A-class soundproofing

Offering guaranteed privacy with an industry-leading 30dB Class A speech level reduction and one of the highest ISO 23351-1 ratings in the industry for office pods.

2 Auto control system

Auto control of the ventilation and lighting systems within the soundproof pod.

3 Optimized lighting

The 4000K ceiling light is Ultra-thin, CRI > 90, 700lm, desktop illuminance up to 300lux.

4 Ventilation system

The dual fan ventilation system can achieve a maximum airflow exceeding 26 l/s, surpassing the global industry standards for office space ventilation.

DEFAULT AIRFLOW preset up to 47 l/s, 100CFM (170 m³/h).

DSS/Dancoo S Standard/ Interior Materials

Interior pet panels: The interior panels are made of high-quality polyester fiber, with a blend of at least three colors that create a visually harmonious effect that blends seamlessly into any office environment.

Its fire resistance performance meets the requirements of B-s1, d0 according to the fire classification standard for building products and construction components BS EN13501-1:2018.

Carpet: The carpet surface is made of nylon filament, featuring permanent antistatic properties, stain resistance, and flame retardancy. Its PE latex backing ensures comfortable walking experience, dimensional stability, and environmental protection.

Table: The tabletop is made of HPL-finished birch plywood that meets FSC requirements, and its steel support structure is fully enclosed in PET felt, seamlessly blending with the wall.

DSS/Dancoo S Standard/Exterior Material and Structure

Exterior: Powder-coated matte steel.

Frames: Structural framework made of solid birch plywood that meets FSC requirements.

Glass: Sound-control laminated glass with built-in sound-insulating interlayer film.

Frameless full-glass door solution

Lock and hinges: Lock has been certified by the EN12209 standard and has passed a 200,000-cycle test of handle movement. The lock body, handle and hinges are available in three colors: natural anodized, black, and white powder coating.

HPL-veneered birch plywood structure door solution

Handle: HPL-veneered birch plywood structure

Hinges and lock: Detachable hinges door with magnetic lock

DSS/Dancoo S Standard/ Power

Power consumption: Default settings 28W. The highest setting 37W. Standby mode 6W.

Input: 100–240 VAC, 10 A, 50–60 Hz

Output ac (power outlet): 100–240VAC, 6.6A, 50–60 Hz

Output usb-c charge port: 25W

Power: OUTLETS 1 × power outlet, Type C Data extension, (Type A +Type C) charge port (Total 25W)

DSS/ Dancoo S Standard / Optional Functionalities

Movability Kit

Allows you to easily relocate your pod without disassembly,

This kit includes 4 castors to make it easier to move the pod.

Occupancy Indication

Lights on the exterior of the pod let you see from a distance whether the pod is free.

dancoo

Quiet Simple Pods

DSS

Dancoo S Standard



MEASUREMENTS

Exterior:

220×100×99 cm (h, w, d)

Interior:

200×80×93 cm (h, w, d)

Doorway:

204.6 × 86 cm (h, w)

WEIGHT

Net Weight: 336 kg

Gross Weight: 428 kg