

DST/Dancoo S Touchscreen / Tech features

1 A-class Soundproofing

Offering guaranteed privacy with an industry-leading 30dB Class A speech level reduction and one of the highest ISO 23351-1 ratings in the industry for office pods.

2 Touchscreen

The touchscreen simplifies the adjustment of the ventilation and lighting systems within the soundproof pod.

3 Optimized Lighting

The adjustable 4000K ceiling light sources permit manual adjustments for personalized lighting preferences. It is Ultra-thin, light-emitting range reaches 280mmX280mm, Color temperature 4000 K, CRI > 90, 1700lm, desktop illuminance up to 500lux.

4 Adjustable Ventilation

The adjustable dual fan featured with damping bracket ventilation system can achieve a maximum airflow exceeding 26 l/s, surpassing the global industry standards for office space ventilation.

DEFAULT AIRFLOW preset up to 47 l/s, 100CFM (170 m³/h), and the airflow can be easily adjusted on the touchscreen. After use, the soundproof pod can ventilate itself in a preset manner.

DST/Dancoo S Touchscreen/ Interior Materials

Interior Panels Pet: The interior panels are made of high-quality polyester fiber, with a blend of at least three colors that create a visually harmonious effect that blends seamlessly into any office environment.

Carpet: Antistatic and stain-resistant low-pile carpet.

Table: HPL-veneered birch plywood tabletop, featuring an internal steel support structure perfectly enclosed by PET felt, which integrates seamlessly with the wall.

DST/Dancoo S Touchscreen/Exterior Material and Structure

Exterior: Powder-coated matte steel.

Frames: Structural framework made of solid birch plywood that meets FSC requirements.

Glass: Sound-control laminated glass with built-in sound-insulating interlayer film.

Frameless full-glass Door Solution

Lock And Hinges: Lock has been certified by the EN12209 standard and has passed a 200,000-cycle test of handle movement. The lock body, handle and hinges are available in three colors: natural anodized, black, and white powder coating.

HPL-Veneered Birch Plywood Structure Door Solution

Handle: HPL-veneered birch plywood structure

Hinges And Lock: Detachable hinges door with magnetic lock

DST/Dancoo S Touchscreen/ Power

Power Consumption: Default settings 28W. The highest setting 37W. Standby mode 6W

Input: 100–240 VAC, 10 A, 50–60 Hz

Output AC (Power Outlet): 100–240VAC, 6.6A, 50–60 Hz

Output USB-C Charge Port: 25W

Power: OUTLETS 1 × power outlet, Type C Data extension, (Type A +Type C) charge port (Total 25W)

DST/ Dancoo S Touchscreen / Optional Functionalities

Movability Kit

Allows you to easily relocate your pod without disassembly

This kit includes 4 castors to make it easier to move the pod

Occupancy Indication

Lights on the exterior of the pod let you see from a distance whether the pod is free

dancoo
Quiet Simple Pods

DST

Dancoo S Touchscreen



MEASUREMENTS

Exterior:

220×100×99 cm (h, w, d)

Interior:

200×80×93 cm (h, w, d)

Doorway:

204.6 × 86 cm (h, w)

Operating space:

240×120×190cm (h, w, d).

WEIGHT

Net Weight: 336 kg

Gross Weight: 428 kg